

无缝弯头尺寸规格

无缝弯头规格尺寸

无缝弯头规格尺寸

不锈钢弯头

R=1.5DN90°

公称通径	外径	弯曲半径	结构长度	壁厚	内径	重量	
DN	D	R	L	S	d		
/mm	/mm	/mm	/mm	/mm	/mm	/(kg/个)	
25	32	38	38	3	26	0.12	
25	34	38	38	3	28	0.14	
32	38	48	48	3.5	31	0.24	
32	42	48	48	3.5	35	0.26	
40	45	60	60	3.5	38	0.36	
40	48	60	60	3.5	41	0.38	
50	57	75	75	4	49	0.64	
50	60	75	75	4	51	0.66	
65	76	98	98	4	68	1.12	
80	89	120	120	4.5	80	1.8	
100	108	150	150	5	98	3	
100	114	150	150	5	104	3.26	
125	133	190	190	6	121	5.6	
125	140	190	190	6	128	6.12	
150	159	225	225	6	147	8.14	
150	168	225	225	6	156	8.62	
200	219	300	300	7	205	17.3	
250	273	375	375	8	257	32	
300	325	450	450	10	305	55	
350	377	525	525	11	355	83	
400	426	600	600	12	402	115.2	
450	480	675	675	18	454	158	
500	530	750	750	14	502	210	

公称通径 外径 弯曲半径 结构长度

DN	/mm	R	L	G30			
/mm		/mm	/mm	壁厚	内径	重量	
			S	d			
			/mm	/mm			
					/(kg/个)		
25	32	38	38	3	26	0.12	
25	34	38	38	3	28	0.14	
32	38	48	48	3.5	31	0.24	
32	42	48	48	3.5	35	0.26	
40	45	60	60	3.5	38	0.36	
40	48	60	60	3.5	41	0.38	
50	57	75	75	4	49	0.64	
50	60	75	75	4	51	0.66	
65	76	98	98	4	68	1.12	
80	89	120	120	4.5	80	1.8	
100	108	150	150	5	98	3	
100	114	150	150	5	104	3.26	
125	133	190	190	6	121	5.6	
125	140	190	190	6	128	6.12	
150	159	225	225	6	147	8.14	
150	168	225	225	6	156	8.62	
200	219	300	300	7	205	17.3	
250	273	375	375	8	257	32	
300	325	450	450	10	305	55	
350	377	525	525	11	355	83	
400	426	600	600	12	402	115.2	
450	480	675	675	18	454	158	
500	530	750	750	14	502	210	